

BELGIQA

ARCHITECTURAL WOOD PRODUCTS

TECHNICAL DATA SHEET - OAK COLLECTION

OAK FOUR

BQO 409 INTENSE TERRA



001 PRODUCT DESCRIPTION

| | | |
|---|--------------|--------------------------------------|
|  | Wood type | European Oak |
|  | Grading | Stormwood |
|  | Core/backing | 2-ply: European oak on birch plywood |
|  | Coating | Reactive stain / colour oil |
|  | Texture | Weathered look & bandsawn effect |
|  | Bevel | Aged |

002 DIMENSIONS

| | Straight | Herringbone |
|---|-----------------------------|-----------------------|
|  Thickness/surface | 19/32" - 5/32" (15/4 mm) | 9/64" (15/4 mm) |
|  Width | 7 31/64" (190 mm) | 5 33/64" (140 mm) |
|  Length | 74 51/64" (1900 mm) | 25 63/64" (700 mm) |

BELGIQA

003 TECHNICAL PERFORMANCE

| | | |
|---|-----------------------------|--|
|  | Norm | En 14342 |
|  | FSC | FSC® (C129924) |
|  | Formaldehyde emission class | Carb2 compliant |
|  | Flammability class | Dfl-s1 |
|  | Underfloor heating | Yes - Warranty certificate available  |
|  | Floor cooling | Yes - Warranty certificate available  |
|  | Thermal conductivity | 0.17 W/mK |
|  | Moisture content | 7 % (+/- 2%) |
|  | Advisory use | Suitable for: residential, commercial, Hospitality, Retail |

004 ADDITIONAL INFORMATION

| | | |
|---|--------------|------------------------|
|  | Installation | Glued down |
|  | Jointing | Tongue and groove |
|  | Sanding | Yes (1 mm per sanding) |



STORMWOOD

Knots : open, filled manually

Cracks : permitted

Sapwood : limited

