

TECHNICAL DATA SHEET

BELGIQA FLEXIBLE VENEER

OAK FOUR

- BQO401 Medium Chalk
- BQO402 Warm Nude
- BQO403 Faded Umber
- BQO404 Soft Taupe
- BQO405 Rich Beige
- BQO406 Smoked White
- BQO407 Faded Brown
- BQO408 Light Terra
- BQO409 Intense Terra
- BQO410 Natural Sand



001 PRODUCT DESCRIPTION

Wood type	European Oak
Finish	Reactive stain / color oil
Composition	Veneer (1,5 mm) on phenolic paper backing
Thickness	1,5 mm
Width	1030 mm
Length	3050 mm

BELGIQA

ARCHITECTURAL WOOD PRODUCTS

002 GRADINGS



RIFT MIXMATCH



MIXMATCH

003 GENERAL INFORMATION

Deviation in dimensions	+10 / -0 mm/m
Deviation in thickness	≤ 0.3 mm
Adhesion wooden top layer	EN204/205, ≥ 1 N/mm2
Internal adhesion	EN319, 0.45 +- 0.05 N/mm2
Density	EN323, 700 +- 10 Kg/m3
Chemical resistance	EN 12720, see next page

004 SAFETY PROPERTIES

Fire classification	EN 13501-1, D-s1-d0
Formaldehyde emission	EN 717-1, E1
REACH	Conform
PCP (Pentachlorophenol)	CEN/TR 14823, <5 Ppm

005 CHEMICAL RESISTANCE

Active substance	Incubation period	Evaluation
Water	24 u	5
Cleaning agent	24 u	5
Ethanol	24 u	5
Acetic Acid	24 u	4
Red wine	24 u	5
Oil	24 u	5
Coffee	24 u	5
Milk	24 u	5
Mustard	24 u	5
Ammonia	2 min	5
Acetone	2 min	5
Assesment	Description	
5	No change	
4	Slight change	
3	Moderate change	
2	Clear change	
1	Strong change	