

## TECHNICAL DATA SHEET - OAK COLLECTION

### OAK THREE

### BQ0 307 FADED BROWN



#### 001 PRODUCT DESCRIPTION

|                                                                                     |              |                                 |
|-------------------------------------------------------------------------------------|--------------|---------------------------------|
|  | Wood type    | European Oak                    |
|  | Grading      | Select/Bis, Elegance or Classic |
|  | Core/backing | 2ply or 3ply engineered plywood |
|  | Coating      | Reactive stain / colour oil     |
|  | Texture      | Light brushed                   |
|  | Bevel        | Micro-V                         |

#### 002 DIMENSIONS

|                                                                                     |                       | Straight                     |                              | Chevron                    |                            | Herringbone                  |                            |
|-------------------------------------------------------------------------------------|-----------------------|------------------------------|------------------------------|----------------------------|----------------------------|------------------------------|----------------------------|
|  | Thickness/<br>surface | 35/64"- 9/64"<br>(14/3,2 mm) | 35/64"- 9/64"<br>(14/3,2 mm) | 19/32"- 5/32"<br>(15/4 mm) | 19/32"- 5/32"<br>(15/4 mm) | 35/64"- 9/64"<br>(14/3,2 mm) | 19/32"- 5/32"<br>(15/4 mm) |
|  | Width                 | 7 31/64"<br>(190 mm)         | 4 23/32"<br>(120 mm)         | 3 35/64"<br>(90 mm)        | 5 33/64"<br>(140 mm)       | 3 35/64"<br>(90 mm)          | 5 33/64"<br>(140 mm)       |
|  | Length                | 74 51/64"<br>(1900 mm)       | 23 5/8"<br>(600 mm)          | 15 3/4"<br>(400 mm)        | 27 9/16"<br>(700 mm)       | 20 5/64"<br>(510 mm)         | 25 63/64"<br>(660 mm)      |

## 003 TECHNICAL PERFORMANCE

---

|                                                                                   |                             |                                                                                                                        |
|-----------------------------------------------------------------------------------|-----------------------------|------------------------------------------------------------------------------------------------------------------------|
|  | Norm                        | En 14342                                                                                                               |
|  | FSC                         | FSC® (C129924)                                                                                                         |
|  | Formaldehyde emission class | Carb2 compliant                                                                                                        |
|  | Flammability class          | Dfl-s1                                                                                                                 |
|  | Underfloor heating          | Yes - Warranty certificate available  |
|  | Floor cooling               | Yes - Warranty certificate available  |
|  | Thermal conductivity        | 0.17 W/mK                                                                                                              |
|  | Moisture content            | 7 % (+/- 2%)                                                                                                           |
|  | Advisory use                | Suitable for: residential, commercial, Hospitality, Retail                                                             |

## 004 ADDITIONAL INFORMATION

---

|                                                                                     |              |                        |
|-------------------------------------------------------------------------------------|--------------|------------------------|
|  | Installation | Glued down             |
|  | Jointing     | Tongue and groove      |
|  | Sanding      | Yes (1 mm per sanding) |



#### SELECT / BIS

**Knots:** minimal

**Cracks:** none

**Sapwood:** limited



#### ELEGANCE

**Knots:** unlimited/filled

**Cracks:** allowed

**Sapwood:** limited



#### CLASSIC

**Knots:** unlimited/filled

**Cracks:** allowed

**Sapwood:** limited

