

BQ0 302 WARM NUDE



European Oak



Select/Bis, Elegance or Classic



2ply or 3ply engineered plywood



Reactive stain / colour oil



Light brushed



Micro-V

$$\frac{\vee}{\wedge}$$

35/64"- 9/64"
(14/3,2 mm)



7 31/64"
(190 mm)

4 23/32"
(120 mm)

3 35/64"
(90 mm)



74 51/64"
(1900 mm)

23 5/8"
(600 mm)

15 3/4"
(400 mm)

19/32"- 5/32"
(15/4 mm)

35/64"- 9/64" 19/32"- 5/32"
(14/3,2 mm) (15/4 mm)

3 35/64" 5 33/64"
(90 mm) (140 mm)

20 5/64"	25 63/64"
(510 mm)	(660 mm)

003 TECHNICAL PERFORMANCE

	Norm	En 14342
	FSC	FSC® (C129924)
	Formaldehyde emission class	Carb2 compliant
	Flammability class	Dfl-s1
	Underfloor heating	Yes - Warranty certificate available 
	Floor cooling	Yes - Warranty certificate available 
	Thermal conductivity	0.17 W/mK
	Moisture content	7 % (+/- 2%)
	Advisory use	Suitable for: residential, commercial, Hospitality, Retail

004 ADDITIONAL INFORMATION

	Installation	Glued down
	Jointing	Tongue and groove
	Sanding	Yes (1 mm per sanding)



SELECT / BIS

Knots: minimal

Cracks: none

Sapwood: limited



ELEGANCE

Knots: unlimited/filled

Cracks: allowed

Sapwood: limited



CLASSIC

Knots: unlimited/filled

Cracks: allowed

Sapwood: limited

