

TECHNICAL DATA SHEET - OAK COLLECTION

OAK NINE

BQ0 903 RECLAIMED CHALK



001 PRODUCT DESCRIPTION



Wood type

European Oak



Grading

1 grading, reclaimed wood



Core/backing

2-ply: Reclaimed oak on plywood



Coating

Multiple reactive stains finished with hardwax oil



Texture

Deep brushed



Bevel

Aged

002 DIMENSIONS

		Straight				
	Thickness/ surface	Thickness: 0.79" / Wear layer: ± 0.24 " (20/+ -6 mm)				
	Width	6.69" (170 mm)	7.48" (190 mm)	8.27" (210 mm)	9.06" (230 mm)	9.84" (250 mm)
	Length	59.06" – 94.49" (1500 - 2400 mm)				

		Herringbone	Chevron
	Thickness/ surface	Thickness: 0.79" / Wear layer: ± 0.24 " (20/+ -6 mm)	
	Width	3.94" (100 mm)	5.51" (140 mm)
	Length	21.65" (550 mm)	21.26" (540 mm)

BELGIQA

www.belgiqa.com | info@belgiqa.com

003 TECHNICAL PERFORMANCE

	Norm	En 14342
	FSC	FSC® (C129924)
	Formaldehyde emission class	Carb2
	Flammability class	Dfl-s1
	Underfloor heating	Yes - Warranty certificate available 
	Floor cooling	Yes - Warranty certificate available 
	Thermal conductivity	0.17 W/mK
	Moisture content	7 % (+/- 2%)
	Advisory use	Suitable for: residential, commercial, Hospitality, Retail

004 ADDITIONAL INFORMATION

	Installation	Glued down
	Jointing	Tongue and groove
	Sanding	Yes (1 mm per sanding)



RECLAIMED

Knots: open, filled manually

Cracks: permitted

Sapwood: limited

