

TECHNICAL DATA SHEET - OAK COLLECTION

OAK FOUR BQ0 408 LIGHT TERRA



001 PRODUCT DESCRIPTION

	Wood type	European Oak
	Grading	Stormwood
	Core/backing	2-ply: European oak on birch plywood
	Coating	Reactive stain / colour oil
	Texture	Weathered look & bandsawn effect
	Bevel	Aged

002 DIMENSIONS

		Straight	Herringbone
	Thickness/surface	19/32" - 5/32" (15/4 mm)	9/64" (15/4 mm)
	Width	7 31/64" (190 mm)	5 33/64" (140 mm)
	Length	74 51/64" (1900 mm)	25 63/64" (700 mm)

003 TECHNICAL PERFORMANCE

	Norm	En 14342
	FSC	FSC® (C129924)
	Formaldehyde emission class	Carb2 compliant
	Flammability class	Dfl-s1
	Underfloor heating	Yes - Warranty certificate available 
	Floor cooling	Yes - Warranty certificate available 
	Thermal conductivity	0.17 W/mK
	Moisture content	7 % (+/- 2%)
	Advisory use	Suitable for: residential, commercial, Hospitality, Retail

004 ADDITIONAL INFORMATION

	Installation	Glued down
	Jointing	Tongue and groove
	Sanding	Yes (1 mm per sanding)



STORMWOOD

Knots : open, filled manually

Cracks : permitted

Sapwood : limited

