

## TECHNICAL DATA SHEET - OAK COLLECTION

### OAK FOUR BQ0 403 FADED UMBER



#### 001 PRODUCT DESCRIPTION

|                                                                                     |              |                                      |
|-------------------------------------------------------------------------------------|--------------|--------------------------------------|
|  | Wood type    | European Oak                         |
|  | Grading      | Stormwood                            |
|  | Core/backing | 2-ply: European oak on birch plywood |
|  | Coating      | Reactive stain / colour oil          |
|  | Texture      | Weathered look & bandsawn effect     |
|  | Bevel        | Aged                                 |

#### 002 DIMENSIONS

|                                                                                     |                   | Straight                    | Herringbone           |
|-------------------------------------------------------------------------------------|-------------------|-----------------------------|-----------------------|
|  | Thickness/surface | 19/32" - 5/32"<br>(15/4 mm) | 9/64"<br>(15/4 mm)    |
|  | Width             | 7 31/64"<br>(190 mm)        | 5 33/64"<br>(140 mm)  |
|  | Length            | 74 51/64"<br>(1900 mm)      | 25 63/64"<br>(700 mm) |

## 003 TECHNICAL PERFORMANCE

---

|                                                                                   |                             |                                                                                                                        |
|-----------------------------------------------------------------------------------|-----------------------------|------------------------------------------------------------------------------------------------------------------------|
|  | Norm                        | En 14342                                                                                                               |
|  | FSC                         | FSC® (C129924)                                                                                                         |
|  | Formaldehyde emission class | Carb2 compliant                                                                                                        |
|  | Flammability class          | Dfl-s1                                                                                                                 |
|  | Underfloor heating          | Yes - Warranty certificate available  |
|  | Floor cooling               | Yes - Warranty certificate available  |
|  | Thermal conductivity        | 0.17 W/mK                                                                                                              |
|  | Moisture content            | 7 % (+/- 2%)                                                                                                           |
|  | Advisory use                | Suitable for: residential, commercial, Hospitality, Retail                                                             |

## 004 ADDITIONAL INFORMATION

---

|                                                                                     |              |                        |
|-------------------------------------------------------------------------------------|--------------|------------------------|
|  | Installation | Glued down             |
|  | Jointing     | Tongue and groove      |
|  | Sanding      | Yes (1 mm per sanding) |



STORMWOOD

Knots : open, filled manually

Cracks : permitted

Sapwood : limited

