

## TECHNICAL DATA SHEET - OAK COLLECTION

### FORGOTTEN WOOD SPECIES BQ W803 INTENSE BARK



#### 001 PRODUCT DESCRIPTION



Wood type

WALNUT



Grading

1 GRADING: MIX PRIME / NATURAL A / NATURAL AB



Core/backing

2-ply: forgotten wood species on birch plywood



Coating

Multiple reactive stains finished with hardwax oil



Texture

Deep brushed



Bevel

Micro V, U, Square, Aged

|                                                                                   |                       |                                      |                               |                                |                                 |
|-----------------------------------------------------------------------------------|-----------------------|--------------------------------------|-------------------------------|--------------------------------|---------------------------------|
|                                                                                   |                       | Straight                             |                               |                                |                                 |
|  | Thickness/<br>surface | 0.59" / 0.16"<br>(15/4 mm)           |                               |                                |                                 |
|  | Width                 | 7.09" / 7.48"<br>(180/190 mm)        | 8.27" / 8.66"<br>(210/220 mm) | 9.84" / 10.24"<br>(250/260 mm) | 11.02" / 11.42"<br>(280/290 mm) |
|  | Length                | 59.06" - 106.30"<br>(1500 - 2700 mm) |                               |                                |                                 |

## 003 TECHNICAL PERFORMANCE

---

|                                                                                   |                             |                                                                                                                        |
|-----------------------------------------------------------------------------------|-----------------------------|------------------------------------------------------------------------------------------------------------------------|
|  | Norm                        | En 14342                                                                                                               |
|  | FSC                         | FSC® (C129924)                                                                                                         |
|  | Formaldehyde emission class | Carb2                                                                                                                  |
|  | Flammability class          | Dfl-s1                                                                                                                 |
|  | Underfloor heating          | Yes - Warranty certificate available  |
|  | Floor cooling               | Yes - Warranty certificate available  |
|  | Thermal conductivity        | 0.17 W/mK                                                                                                              |
|  | Moisture content            | 7 % (+/- 2%)                                                                                                           |
|  | Advisory use                | Suitable for: residential, commercial, Hospitality, Retail                                                             |

## 004 ADDITIONAL INFORMATION

---

|                                                                                     |              |                        |
|-------------------------------------------------------------------------------------|--------------|------------------------|
|  | Installation | Glued down             |
|  | Jointing     | Tongue and groove      |
|  | Sanding      | Yes (1 mm per sanding) |