

BELGIQA

ARCHITECTURAL WOOD PRODUCTS

TECHNICAL DATA SHEET - OAK COLLECTION

OAK EIGHT

BQO 803 SOFT GREY



001 PRODUCT DESCRIPTION



Wood type

European Oak



Grading

Prime/bis, Natural A, Natural AB, Natural B, ART, ART+



Core/backing

2-ply: European oak on birch plywood



Coating

Multiple reactive stains finished with hardwax oil



Texture

Deep brushed



Bevel

Micro V, U, Square, Aged

BELGIQA



002 DIMENSIONS

		Straight			
↘	Thickness/ surface	$9/16'' / 5/32''$ (15/4 mm)			
↕	Width	$2\ 3/4''$ (70 mm)	$3\ 1/2''$ (90 mm)	$6\ 5/16''$ (160 mm)	$7\ 1/16''$ (180 mm)
↔	Length	$3'\ 11\ 1/4'' - 7'\ 2\ 5/8''$ (1200 - 2200 mm)	$4'\ 11\ 1/16'' - 8'\ 10\ 5/16''$ (1500 - 2700 mm)		

		Straight			
↘	Thickness/ surface	$9/16'' / 5/32''$ (15/4 mm)	$9/16'' / 1/8''$ (14/3 mm)	$9/16'' / 5/32''$ (15/4 mm)	
↕	Width	$7\ 7/8''$ (200 mm)	$8\ 11/16''$ (220 mm)	$8\ 11/16''$ (220 mm)	$9\ 7/16''$ (240 mm)
↔	Length	$4'\ 11\ 1/16'' - 8'\ 10\ 5/16''$ (1500 - 2700 mm)			

		Straight	
↘	Thickness/ surface	$9/16'' / 5/32''$ (15/4 mm)	$3/4'' / 5/32''$ (19/4 mm)
↕	Width	$8\ 11/16''$ (260 mm)	$11\ 13/16''$ (300 mm)
↔	Length	$4'\ 11\ 1/16'' - 8'\ 10\ 5/16''$ (1500 - 2700 mm)	

		Herringbone			45° Chevron	
↘	Thickness/ surface	$9/16'' / 5/32''$ (15/4 mm)			$9/16'' / 5/32''$ (15/4 mm)	
↕	Width	$2\ 3/4''$ (70 mm)	$3\ 15/16''$ (100 mm)	$5\ 1/2''$ (140 mm)	$3\ 1/2''$ (90 mm)	$5\ 1/2''$ (140 mm)
↔	Length	$2'\ 3\ 9/16''$ (700 mm)	$1'\ 11\ 5/8''$ (600 mm)	$2'\ 3\ 9/16''$ (700 mm)	$1'\ 8\ 1/16''$ (510 mm)	$2'\ 2''$ (660 mm)

BELGIQA

www.belgiqa.com | info@belgiqa.com



CU-COC-874752

003 TECHNICAL PERFORMANCE

	Norm	En 14342
	FSC	FSC® (C129924)
	Formaldehyde emission class	Carb2
	Flammability class	Dfl-s1
	Underfloor heating	Yes - Warranty certificate available 
	Floor cooling	Yes - Warranty certificate available 
	Thermal conductivity	0.17 W/mK
	Moisture content	7 % (+/- 2%)
	Advisory use	Suitable for: residential, commercial, Hospitality, Retail


004 ADDITIONAL INFORMATION

	Installation	Glued down
	Jointing	Tongue and groove
	Sanding	Yes (1 mm per sanding)



PRIME / BIS

Knots: limited
Cracks: none
Sapwood: none



NATURAL A

Knots: very few
Cracks: none
Sapwood: none



NATURAL B

Knots: unlimited/filled
Cracks: permitted
Sapwood: none



NATURAL AB

Knots: unlimited/filled
Cracks: permitted
Sapwood: none



ART

Natural rustic look
with open/half filled knots and cracks
Top layer: undulating/shrunk knots
Knots: open and/or semi-filled



ART+

Natural rustic look
with open/half filled knots and cracks
Top layer: planed
Knots: open and/or semi-filled

